


- Specifications:
1. Insulation Resistance: 100M Ohms min. (Initial)
  2. Contact Resistance (Initial): 30m Ohm max at 100mA(max) 1KHz.
  3. Dielectric Withstand Voltage: AC 500V, 60Hz for 1 minute.
  4. Insertion Force: 3Kgs max. Extraction Force: 0.08Kgs min.
  5. Humidity Test: 40 $\pm$ 2. 90~95%, 48 hours.

Part Number	Color	Index	Finish
RCJ-021	Black		Black Color
RCJ-022	Red		Red Color
RCJ-023	White		White Color
RCJ-024	Yellow		Yellow Color
RCJ-025	Blue		Blue Color
RCJ-026	Green		Green Color
RCJ-027	Orange		Orange Color

No.	Description	Material	Qty	Finish
5	Insulator B	PBT	1	See Color Index
4	Insulator A	Bakelite	1	See color Index
3	Pin	0.25T Brass	1	90/10 Tin/Lead Plating
2	Mounting Bracket	0.4T Brass	1	90/10 Tin/Lead Plating
1	Phone Jack Shell	0.3T Brass	1	Nickel Plated



PC FILE NAME: rcj-02x.dwg  
 COPYRIGHT 2001 BY CUI INC.

**CUI INC**

9615 SW Allen, Suite 103  
 Beaverton, OR 97005  
 Phone: (503) 643-4899  
 800-275-4899  
 Fax: (503) 372-1266  
 Website: www.cui.com

**TITLE:** RCA Jack, Metal, Vertical, PCB Mnt.

**PART NO.:** RCJ-02X      **UNITS:** Millimeters

**DRAWN BY:** Todd R. White      **APPROVED BY:**      **SCALE:** 3x