

		Virtex-5 LX Platform Optimized for High-performance Logic (1.0 Volt)							Virtex-5 LXT Platform Optimized for High-performance Logic with Low-power Serial Connectivity (1.0 Volt)							Virtex-5 SXT Platform Optimized for DSP with Low-power Serial Connectivity (1.0 Volt)				Virtex-5 FXT Platform Optimized for Embedding Processing with High-Speed Serial Connectivity (1.0 Volt)							
Part Number		XC5VLX30	XC5VLX50	XC5VLX85	XC5VLX110	XC5VLX155	XC5VLX220	XC5VLX330	XC5VLX20T	XC5VLX30T	XC5VLX50T	XC5VLX85T	XC5VLX110T	XC5VLX155T	XC5VLX220T	XC5VLX330T	XC5VSX35T	XC5VSX50T	XC5VSX95T	XC5VSX240T	XC5VFX30T	XC5VFX70T	XC5VFX100T	XC5VFX130T	XC5VFX200T		
EasyPath™ Cost Reduction Solutions <sup>(1)</sup>		—	—	XC5VLX85	XCE5VLX110	XCE5VLX155	XCE5VLX220	XC5VLX330	—	—	—	XCEVLX85T	XCE5VLX110T	XCE5VLX155T	XCE5VLX220T	XC5VLX330T	—	XCE5VSX50T	XCE5VSX95T	XC5VSX240T	—	XCE5VFX70T	XCE5VFX100T	XC5VFX130T	XC5VFX200T		
Logic Resources	Slices <sup>(2)</sup>	4,800	7,200	12,960	17,280	24,320	34,560	51,840	3,120	4,800	7,200	12,960	17,280	24,320	34,560	51,840	5,440	8,160	14,720	37,440	5,120	11,200	16,000	20,480	30,720		
	Logic Cells <sup>(3)</sup>	30,720	46,080	82,944	110,592	155,648	221,184	331,776	19,968	30,720	46,080	82,944	110,592	155,648	221,184	331,776	34,816	52,224	94,208	239,616	32,768	71,680	102,400	131,072	196,608		
	CLB Flip-Flops	19,200	28,800	51,840	69,120	97,280	138,240	207,360	12,480	19,200	28,800	51,840	69,120	97,280	138,240	207,360	21,760	32,640	58,880	149,760	20,480	44,800	64,000	81,920	122,880		
Memory Resources	Maximum Distributed RAM (Kbits)	320	480	840	1,120	1,640	2,280	3,420	210	320	480	840	1,120	1,640	2,280	3,420	520	780	1,520	4,200	380	820	1,240	1,580	2,280		
	Block RAM/FIFO w/ECC (36Kbits each)	32	48	96	128	192	192	288	26	36	60	108	148	212	212	324	84	132	244	516	68	148	228	298	456		
	Total Block RAM (Kbits)	1,152	1,728	3,456	4,608	6,912	6,912	10,368	936	1,296	2,160	3,888	5,328	7,632	7,632	11,664	3,024	4,752	8,784	18,576	2,448	5,328	8,208	10,728	16,416		
Clock Resources	Digital Clock Managers (DCM)	4	12	12	12	12	12	12	2	4	12	12	12	12	12	12	4	12	12	12	4	12	12	12	12		
	Phase Locked Loop (PLL)/PMCD	2	6	6	6	6	6	6	1	2	6	6	6	6	6	6	2	6	6	6	2	6	6	6	6		
I/O Resources <sup>(4)</sup>	Maximum Single-Ended Pins	400	560	560	800	800	800	1,200	172	360	480	480	680	680	680	960	360	480	640	960	360	640	680	840	960		
	Maximum Differential I/O Pairs	200	280	280	400	400	400	600	86	180	240	240	340	340	340	480	180	240	320	480	180	320	340	420	480		
	I/O Standards	HT, LVDS, LVDS6T, RS485, BLVDS, ULVDS, LVPECL, LVCMOS33, LVCMOS25, LVCMOS18, LVCMOS15, LVTTL, PCI33, PCI66, PCI-X, GTL, GTL+, HSTL I (1.2V,1.5V,1.8V), HSTL II (1.5V,1.8V), HSTL III (1.5V,1.8V), HSTL IV (1.5V,1.8V), SSTL2 I, SSTL2 II, SSTL18 I, SSTL18 II																									
Embedded <sup>(5)</sup> Hard IP Resources	DSP48E Slices	32	48	48	64	128	128	192	24	32	48	48	64	128	128	192	192	288	640	1,056	64	128	256	320	384		
	PowerPC® 440 Processor Blocks	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	1	1	2	2	2		
	PCI Express Endpoint Blocks	—	—	—	—	—	—	—	1	1	1	1	1	1	1	1	1	1	1	1	1	3	3	3	4		
	10/100/1000 Ethernet MAC Blocks	—	—	—	—	—	—	—	2	4	4	4	4	4	4	4	4	4	4	4	4	4	4	6	8		
	RocketIO™ GTP Low-Power Transceivers	—	—	—	—	—	—	—	4	8	12	12	16	16	16	24	8	12	16	24	—	—	—	—	—		
	RocketIO™ GTX High-Power Transceivers	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	8	16	16	20	24		
Speed Grades	Commercial	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2	-1, -2	-1, -2	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2	-1, -2, -3	-1, -2, -3	-1, -2	-1, -2	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2		
	Industrial	-1, -2	-1, -2	-1, -2	-1, -2	-1, -2	-1, -2	-1	-1, -2	-1, -2	-1, -2	-1, -2	-1, -2	-1, -2	-1, -2	-1	-1, -2	-1, -2	-1, -2	-1	-1, -2	-1, -2	-1, -2	-1, -2	-1		
Configuration	Configuration Memory (Mbits)	8.4	12.6	21.8	29.1	42.7	53.1	79.7	6.3	9.4	14.1	23.3	31.1	43.0	55.1	82.7	13.3	20.0	35.7	79.6	13.5	27.0	39.4	49.2	70.9		
Package <sup>(6,7)</sup>		Area		Available User I/Os																							
FFA Packages (FF): flip-chip fine-pitch BGA (1.0 mm ball spacing)																											
FF324		19 x 19 mm		220	220																						
FF676		27 x 27 mm		400	400	400	400																				
FF1153		35 x 35 mm			560	560	800	800																			
FF1760		42.5 x 42.5 mm					800	800	800	1200																	
FF323		19 x 19mm										172 (4)	172 (4)														
FF665		27 x 27mm											360 (8)	360 (8)						360 (8)	360 (8)				360 (8)	360 (8)	
FF1136		35 x 35mm											480 (12)	480 (12)	640 (16)	640 (16)				480 (12)	640 (16)				640 (16)	640 (16)	
FF1738		42.5 x 42.5mm													640 (16)	640 (16)	640 (16)	960 (24)						960 (24)	680 (16)	840 (20)	960 (24)

- Notes:
- EasyPath™ solutions provide a conversion-free path for volume production.
  - A single Virtex-5 CLB comprises two slices, with each containing four 6-input LUTs and four Flip-Flops (twice the number found in a Virtex-4 slice), for a total of eight 6-LUTs and eight Flip-Flops per CLB.
  - Virtex-5 logic cell ratings reflect the increased logic capacity offered by the new 6-input LUT architecture.
  - Digitally Controlled Impedance (DCI) is available on I/Os of all devices.
  - One system monitor block included in all devices.
  - Available I/O for each device-package combination: number of SelectIO pins (number of RocketIO transceivers).
  - All products available Pb-free and RoHS-Compliant.