

		Virtex-6 LXT FPGAs Optimized for High-Performance Logic and DSP with Low-Power Serial Connectivity (1.0V, 0.9V)							Virtex-6 SXT FPGAs Optimized for Ultra High-Performance DSP with Low-Power Serial Connectivity (1.0V, 0.9V)		Virtex-6 HXT FPGAs Optimized for Communications Systems that Require Highest-Bandwidth Serial Connectivity (1.0V)			
Part Number		XC6VLX75T	XC6VLX130T	XC6VLX195T	XC6VLX240T	XC6VLX365T	XC6VLX550T	XC6VLX760	XC6VSX315T	XC6VSX475T	XC6VHX250T	XC6VHX255T	XC6VHX380T	XC6VHX565T
EasyPath™ FPGA Cost Reduction Solutions ⁽¹⁾		XCE6VLX75T	XCE6VLX130T	XCE6VLX195T	XCE6VLX240T	XCE6VLX365T	XCE6VLX550T	XCE6VLX760	XCE6VSX315T	XCE6VSX475T	XCE6VHX250T	XCE6VHX255T	XCE6VHX380T	XCE6VHX565T
Logic Resources	Slices ⁽²⁾	11,640	20,000	31,200	37,680	56,880	85,920	118,560	49,200	74,400	39,360	39,600	59,760	88,560
	Logic Cells ⁽³⁾	74,496	128,000	199,680	241,152	364,032	549,888	758,784	314,880	476,160	251,904	253,440	382,464	566,784
	CLB Flip-Flops	93,120	160,000	249,600	301,440	455,040	687,360	948,480	393,600	595,200	314,880	316,800	478,080	708,480
Memory Resources	Maximum Distributed RAM (Kb)	1,045	1,740	3,040	3,650	4,130	6,200	8,280	5,090	7,640	3,040	3,050	4,570	6,370
	Block RAM/FIFO w/ECC (36 Kb each)	156	264	344	416	416	632	720	704	1,064	504	516	768	912
	Total Block RAM (Kb)	5,616	9,504	12,384	14,976	14,976	22,752	25,920	25,344	38,304	18,144	18,567	27,648	32,832
Clock Resources	Mixed-Mode Clock Managers (MMCM)	6	10	10	12	12	18	18	12	18	12	12	18	18
I/O Resources ^(4,5)	Maximum Single-Ended I/O	360	600	600	720	720	1,200	1,200	720	840	320	480	720	720
	Maximum Differential I/O Pairs	180	300	300	360	360	600	600	360	420	160	240	360	360
Embedded Hard IP Resources ⁽⁶⁾	DSP48E1 Slices	288	480	640	768	576	864	864	1,344	2,016	576	576	864	864
	PCI Express® Interface Blocks	1	2	2	2	2	2	-	2	2	4	2	4	4
	10/100/1000 Ethernet MAC Blocks	4	4	4	4	4	4	-	4	4	4	2	4	4
	GTX Low-Power Transceivers	12	20	20	24	24	36	-	24	36	48	24	48	48
	GTH High-Speed Transceivers	-	-	-	-	-	-	-	-	-	-	24	24	24
Speed Grades	Commercial	-L1, -1, -2, -3	-L1, -1, -2, -3	-L1, -1, -2, -3	-L1, -1, -2, -3	-L1, -1, -2, -3	-L1, -1, -2	-L1, -1, -2	-L1, -1, -2, -3	-L1, -1, -2	-1, -2, -3	-1, -2, -3	-1, -2, -3	-1, -2
	Industrial	-L1, -1, -2	-L1, -1, -2	-L1, -1, -2	-L1, -1, -2	-L1, -1, -2	-L1, -1	-L1, -1	-L1, -1, -2	-L1, -1	-1, -2	-1, -2	-1, -2	-1
Configuration	Configuration Memory (Mb)	26.3	43.8	61.6	73.9	96.1	144.1	184.9	104.5	156.7	79.9	79.9	119.8	160.7
Package ⁽⁷⁾		Area												
Available User I/O: SelectIO™ Interface Pins ^(4,5) (GTX Low-Power Transceivers, GTH High-Speed Transceivers)														
FFA Packages (FF): Flip-chip, fine-pitch BGA (1.0 mm ball spacing)														
FF484	23 x 23 mm	240 (8, 0)	240 (8, 0)											
FF784	29 x 29 mm	360 (12, 0)	400 (12, 0)	400 (12, 0)	400 (12, 0)									
FF1156	35 x 35 mm		600 (20, 0)	600 (20, 0)	600 (20, 0)	600 (20, 0)			600 (20, 0)	600 (20, 0)				
FF1759	42.5 x 42.5 mm				720 (24, 0)	720 (24, 0)	840 (36, 0)		720 (24, 0)	840 (36, 0)				
FF1760	42.5 x 42.5 mm						1,200 (0, 0)	1,200 (0, 0)						
FF1154	35 x 35 mm										320 (48, 0)		320 (48, 0)	
FF1155	35 x 35 mm											440 (24, 12)	440 (24, 12)	
FF1923	45 x 45 mm											480 (24, 24)	720 (40, 24)	720 (40, 24)
FF1924	45 x 45 mm												640 (48, 24)	640 (48, 24)

- Notes: 1. EasyPath FPGAs provide a conversion-free, low-risk path for volume production.
 2. A single Virtex-6 FPGA CLB comprises two slices, each containing four 6-input LUTs and eight flip-flops (twice the number found in a Virtex-4 FPGA slice), for a total of eight 6-input LUTs and 16 flip-flops per CLB.
 3. Virtex-6 FPGA logic cell ratings reflect the increased logic capacity offered by the 6-input LUT architecture.
 4. Digitally Controlled Impedance (DCI) is available on I/Os of all devices.
 5. Supported I/O standards include: HT, LVCMOS (1.2V, 1.5V, 1.8V, 2.5V), HSTL I (1.2V,1.5V,1.8V), HSTL II (1.5V,1.8V), HSTL III (1.5V,1.8V), LVDS, Extended LVDS, RSDS, Bus LVDS, LVPECL, SSTL I (1.8V, 2.5V), SSTL II (1.8V, 2.5V), and SSTL (1.5V).
 6. One System Monitor block is included in all devices.
 7. All products are available Pb-free and RoHS-Compliant (FFG).

Important: Verify all data in this document with the device data sheets found at www.xilinx.com