



FT256 - 63/37 (Sn/Pb) SOLDER BALLS
 FTG256 - Sn/Ag/Cu SOLDER BALLS

SYMBOL	MILLIMETERS		
	MIN.	NOM.	MAX.
A	\approx	1.40	1.55
A ₁	0.30	0.40	0.50
D/E	17.00 BSC		
D ₁ /E ₁	15.00 REF		
e	1.00 BSC		
øb	0.40	0.50	0.60
aaa	\approx	\approx	0.20
ccc	\approx	\approx	0.15
ddd	\approx	\approx	0.25
eee	\approx	\approx	0.10
M	16		

NOTES:

1. ALL DIMENSIONS AND TOLERANCES CONFORM TO ASME Y14.5M-1994
2. SYMBOL 'M' IS THE BALL MATRIX SIZE.
3. CONFORMS TO JEDEC MS-034 AAF-1 EXCEPT FOR THE SOLDER BALL SIZE.

PK053_01_021511

Revision History

The following table shows the revision history for this document.

Date	Version	Description of Revisions
03/23/05	1.2.1	Update.
10/05/07	1.3	Changed the A1 minimum dimension to 0.30 mm.
03/23/11	1.4	Changed the FTG256 solder ball description.

Notice of Disclaimer

Xilinx regards this materials data to be correct but makes no guarantee as to its accuracy or completeness, including, but not limited to, with respect to its compliance with applicable environmental laws and regulations. Xilinx subcontracts the production, test and assembly of hardware devices to independent third-party vendors and materials suppliers ("Contractors"). All data provided hereunder is based on information received from Contractors. Xilinx has not independently verified the accuracy or completeness of this information which is provided solely for your reference in connection with the use of Xilinx products.