

Improving Area and Resource Utilization Lab

Introduction

This lab introduces various techniques and directives which can be used in Vivado HLS to improve design performance as well as area and resource utilization. The design under consideration performs discrete cosine transformation (DCT) on an 8x8 block of data.

Objectives

After completing this lab, you will be able to:


- Add directives in your design
- Improve performance using PIPELINE directive
- Distinguish between DATAFLOW directive and Configuration Command functionality
- Apply memory partitions techniques to improve resource utilization

Procedure

This lab is separated into steps that consist of general overview statements that provide information on the detailed instructions that follow. Follow these detailed instructions to progress through the lab.

This lab comprises 9 primary steps: You will validate the design in Vivado HLS command prompt, create a new project using Vivado HLS GUI, synthesize the design, run RTL simulation, apply PIPELINE directive to improve performance, improve the memory bandwidth by applying PARTITION directive, apply DATAFLOW directive, apply INLINE directive, and finally apply RESHAPE directive.

General Flow for this Lab



Validate the Design from Command Line

Step 1

1-1. Validate your design from Vivado HLS command line.

1-1-1. Launch Vivado HLS: Select **Start > All Programs > Xilinx Design Tools > Vivado 2014.4 > Vivado HLS > Vivado HLS 2014.4 Command Prompt**.

1-1-2. In the Vivado HLS Command Prompt, change directory to **c:\xup\hls\labs\lab3**.

1-1-3. A self-checking program (dct_test.c) is provided. Using that we can validate the design. A Makefile is also provided. Using the Makefile, the necessary source files can be compiled and the compiled program can be executed. In the Vivado HLS Command Prompt, type **make** to compile and execute the program.

```
c:\xup\hls\labs\lab3>make
gcc -ggdb -w -I/c/Xilinx/Vivado_HLS/2012.2/include -c -o dct.o dct.c
gcc -ggdb -w -I/c/Xilinx/Vivado_HLS/2012.2/include -c -o dct_test.o dct_test.c

gcc -lm -lstdc++ dct.o dct_test.o -o dct
./dct
  ***  ***  ***  ***
  Results are good
  ***  ***  ***  ***
c:\xup\hls\labs\lab3>
```

Figure 1. Validating the design

Note that the source files (dct.c and dct_test.c) are compiled, then the dct executable program was created, and then it was executed. The program tests the design and outputs **Results are good** message.

1-1-4. Close the command prompt window by typing **exit**.

Create a New Project

Step 2

2-1. Create a new project in Vivado HLS GUI targeting XC7Z020CLG484-1 (ZedBoard) or XC7Z010CLG400-1 (Zybo).

2-1-1. Launch Vivado HLS: Select **Start > All Programs > Xilinx Design Tools > Vivado 2014.4 > Vivado HLS > Vivado HLS 2014.4**

2-1-2. In the Vivado HLS GUI, select **File > New Project**. The New Vivado HLS Project wizard opens.

2-1-3. Click **Browse...** button of the Location field and browse to **c:\xup\hls\labs\lab3** and then click **OK**.

2-1-4. For Project Name, type **dct.prj**

2-1-5. Click **Next**.

- 2-1-6.** In the *Add/Remove Files* for the source files, type **dct** as the function name (the provided source file contains the function, to be synthesized, called dct).
- 2-1-7.** Click the **Add Files...** button, select *dct.c* file from the **c:\xup\hls\labs\lab3** folder, and then click **Open**.
- 2-1-8.** Click **Next**.
- 2-1-9.** In the *Add/Remove Files* for the testbench, click the **Add Files...** button, select *dct_test.c*, *in.dat*, *out.golden.dat* files from the **c:\xup\hls\labs\lab3** folder and click **Open**.
- 2-1-10.** Click **Next**.
- 2-1-11.** In the *Solution Configuration* page, leave Solution Name field as **solution1** and set the clock period as **10** (for ZedBoard) or **8** (for Zybo). Leave Uncertainty field blank as it will take 1.25 as the default value for ZedBoard and 1 for Zybo.
- 2-1-12.** Click on Part's Browse button, and select the following filters, using the *Parts Specify* option, to select **xc7z020clg484-1** (ZedBoard) or **xc7z010clg400-1** (Zybo), and click **OK**:
 Family: **Zynq**
 Sub-Family: **Zynq**
 Package: **clg484** (ZedBoard) or **clg400** (Zybo)
 Speed Grade: **-1**
- 2-1-13.** Click **Finish**.
- 2-1-14.** Double-click on the **dct.c** under the *source* folder to open its content in the information pane.

```

78 void dct(short input[N], short output[N])
79 {
80
81     short buf_2d_in[DCT_SIZE][DCT_SIZE];
82     short buf_2d_out[DCT_SIZE][DCT_SIZE];
83
84     // Read input data. Fill the internal buffer.
85     read_data(input, buf_2d_in);
86
87     dct_2d(buf_2d_in, buf_2d_out);
88
89     // Write out the results.
90     write_data(buf_2d_out, output);
91 }

```

Figure 2. The design under consideration

The top-level function `dct`, is defined at line 78. It implements 2D DCT algorithm by first processing each row of the input array via a 1D DCT then processing the columns of the resulting array through the same 1D DCT. It calls `read_data`, `dct_2d`, and `write_data` functions.

The `read_data` function is defined at line 54 and consists of two loops – `RD_Loop_Row` and `RD_Loop_Col`. The `write_data` function is defined at line 66 and consists of two loops to perform writing the result. The `dct_2d` function, defined at line 23, calls `dct_1d` function and performs transpose.

Finally, `dct_1d` function, defined at line 4, uses `dct_coeff_table` and performs the required function by implementing a basic iterative form of the 1D Type-II DCT algorithm. Following figure shows

the function hierarchy on the left-hand side, the loops in the order they are executed and the flow of data on the right-hand side.




Figure 3. Design hierarchy and dataflow

Synthesize the Design

Step 3

3-1. Synthesize the design with the defaults. View the synthesis results and answer the question listed in the detailed section of this step.

3-1-1. Select **Solution > Run C Synthesis > Active Solution** or click on the  button to start the synthesis process.

3-1-2. When synthesis is completed, several report files will become accessible and the Synthesis Results will be displayed in the information pane.

Note that the Synthesis Report section in the Explorer view only shows dct_1d.rpt, dct_2d.rpt, and dct.rpt entries. The read_data and write_data functions reports are not listed. This is because these two functions are inlined. Verify this by scrolling up into the Vivado HLS Console view.

```

Vivado HLS Console
@I [HLS-10] Analyzing design file 'dct.c' ...
@I [HLS-10] Validating synthesis directives ...
@I [HLS-10] Starting code transformations ...
@I [HLS-10] Checking synthesizability ...
@I [XFORM-602] Inlining function 'read_data' into 'dct' (dct.c:85) automatically.
@I [XFORM-602] Inlining function 'write_data' into 'dct' (dct.c:90) automatically.
@I [XFORM-602] Inlining function 'read_data' into 'dct' (dct.c:85) automatically.
@I [XFORM-602] Inlining function 'write_data' into 'dct' (dct.c:90) automatically.
@I [HLS-111] Elapsed time: 4.55 seconds; current memory usage: 69.8 MB.
    
```

Figure 4. Inlining of read_data and write_data functions

3-1-3. The Synthesis Report shows the performance and resource estimates as well as estimated latency in the design. Note that the design is not optimized nor is pipelined.

Performance Estimates

- Timing (ns)
 - Summary

Clock	Target	Estimated	Uncertainty
default	10.00	6.38	1.25

8.00 for Zybo
- Latency (clock cycles)
 - Summary

Latency		Interval		
min	max	min	max	Type
3959	3959	3960	3960	none
 - Detail
 - Instance
 - Loop

Loop Name	Latency		Iteration Latency	Initiation Interval		Trip Count	Pipelined
	min	max		achieved	target		
- RD_Loop_Row	144	144	18	-	-	8	no
+ RD_Loop_Col	16	16	2	-	-	8	no
- WR_Loop_Row	144	144	18	-	-	8	no
+ WR_Loop_Col	16	16	2	-	-	8	no

Figure 5. Synthesis report

3-1-4. Using scroll bar on the right, scroll down into the report and answer the following question.

Question 1

- Estimated clock period: _____
- Worst case latency: _____
- Number of DSP48E used: _____
- Number of BRAMs used: _____
- Number of FFs used: _____
- Number of LUTs used: _____

3-1-5. The report also shows the top-level interface signals generated by the tools.

Interface					
Summary					
RTL Ports	Dir	Bits	Protocol	Source Object	C Type
ap_clk	in	1	ap_ctrl_hs	dct	return value
ap_rst	in	1	ap_ctrl_hs	dct	return value
ap_start	in	1	ap_ctrl_hs	dct	return value
ap_done	out	1	ap_ctrl_hs	dct	return value
ap_idle	out	1	ap_ctrl_hs	dct	return value
ap_ready	out	1	ap_ctrl_hs	dct	return value
input_r_address0	out	6	ap_memory	input_r	array
input_r_ce0	out	1	ap_memory	input_r	array
input_r_q0	in	16	ap_memory	input_r	array
output_r_address0	out	6	ap_memory	output_r	array
output_r_ce0	out	1	ap_memory	output_r	array
output_r_we0	out	1	ap_memory	output_r	array
output_r_d0	out	16	ap_memory	output_r	array

Figure 6. Generated interface signals

You can see `ap_clk`, `ap_rst` are automatically added. The `ap_start`, `ap_done`, `ap_idle`, and `ap_ready` are top-level signals used as handshaking signals to indicate when the design is able to accept next computation command (`ap_idle`), when the next computation is started (`ap_start`), and when the computation is completed (`ap_done`). The top-level function has input and output arrays, hence an `ap_memory` interface is generated for each of them.

3-1-6. Open `dct_1d.rpt` and `dct_2d.rpt` files either using the Explorer view or by using a hyperlink at the bottom of the `dct.rpt` in the information view. The report for `dct_2d` clearly indicates that most of this design cycles (3668) are spent doing the row and column DCTs. Also the `dct_1d` report indicates that the latency is 209 clock cycles $((24+2)*8+1)$.

Run Co-Simulation

Step 4

4-1. Run the Co-simulation, selecting SystemC. Verify that the simulation passes.

4-1-1. Select **Solution > Run C/RTL Cosimulation** or click on the button to open the dialog box so the desired simulations can be run.

A C/RTL Co-simulation Dialog box will open.

4-1-2. Select the SystemC option, and click **OK** to run the SystemC simulation.

The RTL Co-simulation will run, generating and compiling several files, and then simulating the design. In the console window you can see the progress and also a message that the test is passed.

Cosimulation Report for 'dct'

Result							
RTL	Status	Latency			Interval		
		min	avg	max	min	avg	max
VHDL	NA	NA	NA	NA	NA	NA	NA
Verilog	NA	NA	NA	NA	NA	NA	NA
SystemC	Pass	3959	3959	3959	3960	3960	3960

```

INFO: [Common 17-206] Exiting xsim at Tue Jan 13 14:45:45 2015...
@I [SIM-316] Starting C post checking ...
*** **
Results are good
*** **
@I [SIM-1000] *** C/RTL co-simulation finished: PASS ***
@I [LIC-101] Checked in feature [HLS]

```

Figure 7. RTL Co-cimulation results

Apply PIPELINE Directive

Step 5

5-1. Create a new solution by copying the previous solution settings. Apply the PIPELINE directive to DCT_Inner_Loop, Xpose_Row_Inner_Loop, Xpose_Col_Inner_Loop, RD_Loop_Col, and WR_Loop_Col. Generate the solution and analyze the output.

5-1-1. Select **Project > New Solution** or click on () from the tools bar buttons.

5-1-2. A *Solution Configuration* dialog box will appear. Click the **Finish** button (with *copy from Solution1* selected).

5-1-3. Make sure that the **dct.c** source is opened in the information pane and click on the **Directive** tab.

5-1-4. Select **DCT_Inner_Loop** of the **dct_1d** function in the Directive pane, right-click on it and select *Insert Directive...*

5-1-5. A pop-up menu shows up listing various directives. Select **PIPELINE** directive.

5-1-6. Leave **II** (Initiation Interval) blank as Vivado HLS will try for an **II=1**, one new input every clock cycle.

5-1-7. Click **OK**.

5-1-8. Similarly, apply the **PIPELINE** directive to **Xpose_Row_Inner_Loop** and **Xpose_Col_Inner_Loop** of the **dct_2d** function, and **RD_Loop_Col** of the **read_data** function, and **WR_Loop_Col** of the **write_data** function. At this point, the Directive tab should look like as follows.




Figure 8. PIPELINE directive applied

5-1-9. Click on the **Synthesis** button.

5-1-10. When the synthesis is completed, select **Project > Compare Reports...** or click on  to compare the two solutions.

5-1-11. Select *Solution1* and *Solution2* from the **Available Reports**, click on the **Add>>** button, and then click **OK**.

5-1-12. Observe that the latency reduced from 3959 to 1978 clock cycles.




Figure 9. Performance comparison after pipelining

5-1-13. Scroll down in the comparison report to view the resources utilization. Observe that the FFs and LUTs utilization increased whereas BRAM and DSP48E remained same.




Figure 10. Resources utilization after pipelining

5-2. Open the Analysis perspective and determine where most of the clock cycles are spend, i.e. where are the large latencies.

5-2-1. Click on the *Analysis* perspective button.

5-2-2. In the Module Hierarchy, select the dct entry and observe the RD_Loop_Row_RD_Loop_Col and WR_Loop_Row_WR_Loop_Col entries. These are two nested loops flattened and given the new names formed by appending inner loop name to the out loop name. You can also verify this by looking in the Console view message.

```
@I [XFORM-602] Inlining function 'read_data' into 'dct' (dct.c:85) automatically.
@I [XFORM-602] Inlining function 'write_data' into 'dct' (dct.c:90) automatically.
@I [XFORM-541] Flattening a loop nest 'RD_Loop_Row' (dct.c:59) in function 'dct'.
@I [XFORM-541] Flattening a loop nest 'WR_Loop_Row' (dct.c:71) in function 'dct'.
@I [XFORM-541] Flattening a loop nest 'Xpose_Row_Outer_Loop' (dct.c:37) in function 'dct_2d'.
@I [XFORM-541] Flattening a loop nest 'Xpose_Col_Outer_Loop' (dct.c:48) in function 'dct_2d'.
```

Figure 11. The console view content indicating loops flattening

Module Hierarchy

	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
dct	5	1	249	502	1850	1851	none
dct_dct_2d	3	1	188	348	1717	1717	none

Performance Profile

	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
dct	-	1850	1851	-	-
RD_Loop_Row_RD_Loop_Col	yes	64	1	2	64
WR_Loop_Row_WR_Loop_Col	yes	64	1	2	64

(a) ZedBoard

Module Hierarchy

	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
dct	5	1	283	506	1854	1855	none
dct_dct_2d	3	1	208	350	1719	1719	none
dct_dct_1d	0	1	111	128	97	97	none

Performance Profile

	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
dct	-	1854	1855	-	-
RD_Loop_Row_RD_Loop_Col	yes	65	1	3	64
WR_Loop_Row_WR_Loop_Col	yes	65	1	3	64

(b) Zybo

Figure 12. The performance profile at the dct function level

5-2-3. In the Module Hierarchy tab, expand **dct > dct_2d > dct_1d**. Notice that the most of the latency occurs is in **dct_2d** function.

5-2-4. In the Module Hierarchy tab, expand **dct > dct_2d > dct_1d**, select the **dct_1d** entry and notice that there still hierarchy exists in the module, i.e. it is not flattened.

Module Hierarchy

	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
dct	5	1	249	502	1850	1851	none
dct_dct_2d	3	1	188	348	1717	1717	none
dct_dct_1d	0	1	111	128	97	97	none

Performance Profile

	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
dct_dct_1d	-	97	97	-	-
DCT_Outer_Loop	no	96	-	12	8
DCT_Inner_Loop	yes	9	1	3	8

(a) ZedBoard

Module Hierarchy							
	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
▲ ● dct	5	1	283	506	1854	1855	none
▲ ● dct_dct_2d	3	1	208	350	1719	1719	none
● dct_dct_1d	0	1	111	128	97	97	none

Performance Profile					
	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
▲ ● dct_dct_1d	-	97	97	-	-
▲ ● DCT_Outer_Loop	no	96	-	12	8
● DCT_Inner_Loop	yes	9	1	3	8

(b) Zybo

Figure 13. The dct_1d function performance profile

5-2-5. In the Performance Profile tab, select the DCT_Inner_Loop entry, right-click on the node_60 (write) block in the C3 state in the Performance view, and select Goto Source. Notice that line 19 is highlighted which is preventing the flattening of the DCT_Outer_Loop.

Figure 14. Understanding what is preventing DCT_Outer_Loop flattening

5-2-6. Switch to the *Synthesis* perspective.

5-3. **Create a new solution by copying the previous solution settings. Apply fine-grain parallelism of performing multiply and add operations of the inner loop of dct_1d using PIPELINE directive by moving the PIPELINE directive from inner loop to the outer loop of dct_1d. Generate the solution and analyze the output.**

5-3-1. Select **Project > New Solution**.

5-3-2. A *Solution Configuration* dialog box will appear. Click the **Finish** button (with Solution2 selected).

5-3-3. Select PIPELINE directive of **DCT_Inner_Loop** of the **dct_1d** function in the Directive pane, right-click on it and select *Remove Directive*.

5-3-4. Select **DCT_Outer_Loop** of the **dct_1d** function in the Directive pane, right-click on it and select *Insert Directive...*

5-3-5. A pop-up menu shows up listing various directives. Select **PIPELINE** directive.

5-3-6. Click **OK**.




Figure 15. PIPELINE directive applied to DCT_Outer_Loop

By pipelining an outer loop, all inner loops will be unrolled automatically (if legal), so there is no need to explicitly apply an UNROLL directive to DCT_Inner_Loop. Simply move the pipeline to the outer loop: the nested loop will still be pipelined but the operations in the inner-loop body will operate concurrently.

5-3-7. Click on the **Synthesis** button.

5-3-8. When the synthesis is completed, select **Project > Compare Reports...** to compare the two solutions.

5-3-9. Select *Solution2* and *Solution3* from the **Available Reports**, click on the **Add>>** button, and then click **OK**.

5-3-10. Observe that the latency reduced from 1850 to 874 clock cycles for ZedBoard (1855 to 878 for Zybo).

Performance Estimates				Performance Estimates			
☐ Timing (ns)				☐ Timing (ns)			
Clock		solution3	solution2	Clock		solution3	solution2
default	Target	10.00	10.00	default	Target	8.00	8.00
	Estimated	7.38	7.36		Estimated	6.38	6.38
☐ Latency (clock cycles)				☐ Latency (clock cycles)			
		solution3	solution2			solution3	solution2
Latency	min	874	1850	Latency	min	878	1854
	max	874	1850		max	878	1854
Interval	min	875	1851	Interval	min	879	1855
	max	875	1851		max	879	1855

(a) ZedBoard

(b) Zybo

Figure 16. Performance comparison after pipelining

5-3-11. Scroll down in the comparison report to view the resources utilization. Observe that the utilization of all resources (except BRAM) increased. Since the DCT_Inner_Loop was unrolled, the parallel computation requires 8 DSP48E.

Utilization Estimates			Utilization Estimates		
	solution3	solution2		solution3	solution2
BRAM_18K	5	5	BRAM_18K	5	5
DSP48E	8	1	DSP48E	8	1
FF	722	249	FF	785	283
LUT	577	502	LUT	565	506

(a) ZedBoard (b) Zybo

Figure 17. Resources utilization after pipelining

5-3-12. Open dct_1d report and observe that the pipeline initiation interval (II) is four (4) cycles, not one (1) as might be hoped and there are now 8 BRAMs being used for the coefficient table.

Looking closely at the synthesis log, notice that the coefficient table was automatically partitioned, resulting in 8 separate ROMs: this helped reduce the latency by keeping the unrolled computation loop fed, however the input arrays to the dct_1d function were not automatically partitioned.

The reason the II is four (4) rather than the eight (8) one might expect, is because Vivado HLS automatically uses dual-port RAMs, when beneficial to scheduling operations.

Performance Estimates

▣ **Timing (ns)** For Zybo it will be 8.00 and 6.38

▣ **Summary**

Clock	Target	Estimated	Uncertainty
default	10.00	7.38	1.25

▣ **Latency (clock cycles)**

▣ **Summary**

Latency		Interval		
min	max	min	max	Type
36	36	36	36	none

▣ **Detail**

⊕ **Instance**

▣ **Loop**

Loop Name	Latency		Iteration Latency	Initiation Interval		Trip Count	Pipelined
	min	max		achieved	target		
- DCT_Outer_Loop	34	34	7	4	1	8	yes

Figure 18. Increased resource utilization of dct_1d

```
@I [HLS-10] Starting code transformations ...
@I [XFORM-502] Unrolling all sub-loops inside loop 'DCT_Outer_Loop' (dct.c:13) in function 'dct_1d' for pipelining.
@I [XFORM-501] Unrolling loop 'DCT_Inner_Loop' (dct.c:15) in function 'dct_1d' completely.
@I [XFORM-102] Partitioning array 'dct_coeff_table' in dimension 2 automatically.
@I [XFORM-602] Inlining function 'read_data' into 'dct' (dct.c:85) automatically.
@I [XFORM-602] Inlining function 'write_data' into 'dct' (dct.c:90) automatically.
@I [XFORM-11] Balancing expressions in function 'dct_1d' (dct.c:4)...8 expression(s) balanced.
@I [XFORM-541] Flattening a loop nest 'RD_Loop_Row' (dct.c:59) in function 'dct'.
@I [XFORM-541] Flattening a loop nest 'WR_Loop_Row' (dct.c:71) in function 'dct'.
@I [XFORM-541] Flattening a loop nest 'Xpose_Row_Outer_Loop' (dct.c:37) in function 'dct_2d'.
@I [XFORM-541] Flattening a loop nest 'Xpose_Col_Outer_Loop' (dct.c:48) in function 'dct_2d'.
@I [HLS-111] Elapsed time: 4.477 seconds; current memory usage: 56.2 MB.
@I [HLS-10] Starting hardware synthesis ...
@I [HLS-10] Synthesizing 'dct' ...
```

Figure 19. Automatic partitioning of dct_coeff_table

```
@I [HLS-10] -----
@I [HLS-10] -- Scheduling module 'dct_dct_1d'
@I [HLS-10] -----
@I [SCHED-11] Starting scheduling ...
@I [SCHED-61] Pipelining loop 'DCT_Outer_Loop'.
@W [SCHED-69] Unable to schedule 'load' operation ('src_load_1', dct.c:17) on array 'src' due to limited memory ports.
@I [SCHED-61] Pipelining result: Target II: 1, Final II: 4, Depth: 7.
@I [SCHED-11] Finished scheduling.
@I [HLS-111] Elapsed time: 0.19 seconds; current memory usage: 71.8 MB.
```

Figure 20. Initiation interval of 4

5-4. Perform design analysis by switching to the Analysis perspective and looking at the dct_1d performance view.

- 5-4-1. Switch to the Analysis perspective, expand the *Module Hierarchy* entries, and select the *dct_1d* entry.
- 5-4-2. Expand, if necessary, the **Profile** tab entries and notice that the *DCT_Outer_Loop* is now pipelined and there is no *DCT_Inner_Loop* entry.

	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
dct	5	8	722	577	874	875	none
dct_dct_2d	3	8	661	422	741	741	none
dct_dct_1d	0	8	584	184	36	36	none

	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
dct_dct_1d	-	36	36	-	-
DCT_Outer_Loop	yes	34	4	7	8

(a) ZedBoard

	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
dct	5	8	785	565	878	879	none
dct_dct_2d	3	8	710	408	743	743	none
dct_dct_1d	0	8	613	168	36	36	none

	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
dct_dct_1d	-	36	36	-	-
DCT_Outer_Loop	yes	34	4	7	8

(b) Zybo

Figure 21. DCT_Outer_Loop flattening

- 5-4-3. Select the `dct_1d` entry in the Module Hierarchy tab and observe that the `DCT_Outer_Loop` spans over eight states in the Performance view.

Current Module : `dct > dct dct 2d > dct dct 1d`

	Operation\Control S...	C0	C1	C2	C3	C4	C5	C6	C7
1	tmp 11 read(read)								
2	tmp 1 read(read)								
3	tmp 7 ()								
4	tmp 10 ()								
5	tmp 13 ()								
6	tmp 15 ()								
7	tmp 17 ()								
8	tmp 19 ()								
9	tmp 21 ()								
1...	⊞DCT Outer Loop								

Figure 22. The Performance view of the `DCT_Outer_Loop` function

- 5-4-4. Select the **Resource** tab, expand the *Memory Ports* entry and observe that the memory accesses on BRAM *src* are being used to the maximum in every clock cycle. (At most a BRAM can be dual-port and both ports are being used). This is a good indication the design may be bandwidth limited by the memory resource.

Current Module : `dct > dct dct 2d > dct dct 1d`

	Resource\Control Step	C0	C1	C2	C3	C4	C5	C6	C7
1	⊞I/O Ports								
2	tmp 1	read							
3	tmp 11	read							
4	src (p0)		read	read	read	read			
5	src (p1)		read	read	read	read			
6	dst (p0)								write
7	⊞Memory Ports								
8	src (p0)		read	read	read	read			
9	src (p1)		read	read	read	read			
10	dct coeff tabl...		read						
11	dct coeff tabl...		read						
12	dct coeff tabl...			read					
13	dct coeff tabl...				read				
14	dct coeff tabl...				read				
15	dct coeff tabl...				read				
16	dct coeff tabl...				read				
17	dct coeff tabl...				read				
18	dst (p0)								write
1...	⊞Expressions								

Performance Resource

Figure 23. The Resource tab

- 5-4-5. Switch to the *Synthesis* perspective.

Improve Memory Bandwidth

Step 6

6-1. Create a new solution by copying the previous solution (Solution3) settings. Apply **ARRAY_PARTITION** directive to **buf_2d_in** of **dct** (since the bottleneck was on **src** port of the **dct_1d** function, which was passed via **in_block** of the **dct_2d** function, which in turn was passed via **buf_2d_in** of the **dct** function) and **col_inbuf** of **dct_2d**. Generate the solution.

6-1-1. Select **Project > New Solution** to create a new solution.

6-1-2. A *Solution Configuration* dialog box will appear. Click the **Finish** button (with Solution3 selected).

6-1-3. With **dct.c** open, select **buf_2d_in** array of the **dct** function in the Directive pane, right-click on it and select *Insert Directive...*

The *buf_2d_in* array is selected since the bottleneck was on *src* port of the *dct_1d* function, which was passed via *in_block* of the *dct_2d* function, which in turn was passed via *buf_2d_in* of the *dct* function).

6-1-4. A pop-up menu shows up listing various directives. Select **ARRAY_PARTITION** directive.

6-1-5. Make sure that the **type** is *complete*. Enter **2** in the *dimension* field and click **OK**.




Figure 24. Applying **ARRAY_PARTITION** directive to memory buffer

6-1-6. Similarly, apply the *ARRAY_PARTITION* directive with dimension of 2 to the **col_inbuf** array.

6-1-7. Click on the **Synthesis** button.

- 6-1-8. When the synthesis is completed, select **Project > Compare Reports...** to compare the two solutions.
- 6-1-9. Select *Solution3* and *Solution4* from the **Available Reports**, and click on the **Add>>** button.
- 6-1-10. Observe that the latency reduced from 870 to 508 clock cycles for ZedBoard (878 to 528 for Zybo).




Figure 25. Performance comparison after array partitioning

- 6-1-11. Scroll down in the comparison report to view the resources utilization. Observe the increase in the FF resource utilization (almost double).




Figure 26. Resources utilization after array partitioning

- 6-1-12. Expand the **Loop** entry in the **dct.rpt** entry and observe that the Pipeline II is now *1*.
- 6-2. Perform resource analysis by switching to the Analysis perspective and looking at the dct resources profile view.**
 - 6-2-1. Switch to the Analysis perspective, expand the Module Hierarchy entries, and select the **dct** entry.
 - 6-2-2. Select the **Resource Profile** tab.
 - 6-2-3. Expand the Memories and Expressions entries and observe that the most of the resources are consumed by instances. The **buf_2d_in** array is partitioned into multiple memories and most of the operations are done in addition and comparison.

Module Hierarchy							
	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
▲ dct	3	8	1358	675	508	509	none
▶ dct_dct_2d	2	8	1038	478	373	373	none
● dct_read_data	0	0	28	62	66	66	none

Performance Profile								Resource Profile	
	BRAM	DSP	FF	LUT	Bits P0	Bits P1	Bits P2	Banks/Depth	
▲ dct	3	8	1358	675					
▶ I/O Ports(2)					32				
▲ Instances(2)	2	8	1066	540					
◆ grp_dct_dct_2_2		8	1038	478					
◆ grp_dct_read_0		0	28	62					
▲ Memories(9)	1		256	16	144			9	
◆ buf_2d_out_U_1			0	0	16			1	
◆ buf_2d_in_6_U_0			32	2	16			1	
◆ buf_2d_in_5_U_0			32	2	16			1	
◆ buf_2d_in_4_U_0			32	2	16			1	
◆ buf_2d_in_3_U_0			32	2	16			1	
◆ buf_2d_in_7_U_0			32	2	16			1	
◆ buf_2d_in_2_U_0			32	2	16			1	
◆ buf_2d_in_1_U_0			32	2	16			1	
◆ buf_2d_in_0_U_0			32	2	16			1	
▶ Expressions(9)	0	0	0	50	42	35	8		
▶ Registers(11)			36		36				
▶ FIFO(0)	0		0	0	0			0	
▶ Multiplexers(33)	0		0	69	69			0	

(a) ZedBoard

Module Hierarchy							
	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
▲ dct	3	8	1414	679	528	529	none
▶ dct_dct_2d	2	8	1077	480	391	391	none
● dct_read_data	0	0	38	63	67	67	none

Performance Profile								
	BRAM	DSP	FF	LUT	Bits P0	Bits P1	Bits P2	Banks/Depth
▲ dct	3	8	1414	679				
▶ I/O Ports(2)					32			
▶ Instances(2)	2	8	1115	543				
▲ Memories(9)	1		256	16	144			9
◆ buf_2d_out_U	1		0	0	16			1
◆ buf_2d_in_6_U	0		32	2	16			1
◆ buf_2d_in_5_U	0		32	2	16			1
◆ buf_2d_in_4_U	0		32	2	16			1
◆ buf_2d_in_3_U	0		32	2	16			1
◆ buf_2d_in_7_U	0		32	2	16			1
◆ buf_2d_in_2_U	0		32	2	16			1
◆ buf_2d_in_1_U	0		32	2	16			1
◆ buf_2d_in_0_U	0		32	2	16			1
▲ Expressions(9)	0	0	0	50	42	35	8	
▶ +	0	0	0	29	29	17	0	
▶ icmp	0	0	0	13	11	13	0	
▶ Select	0	0	0	8	2	5	8	
▶ Registers(15)			43		43			
▶ FIFO(0)	0		0	0	0			0
▶ Multiplexers(34)	0		0	70	70			0

(b) Zybo

Figure 27. Resource profile after partitioning buffers

6-2-4. Switch to the *Synthesis* perspective.

Apply DATAFLOW Directive

Step 7

7-1. Create a new solution by copying the previous solution (Solution4) settings. Apply the DATAFLOW directive to improve the throughput. Generate the solution and analyze the output.

7-1-1. Select **Project > New Solution**.

7-1-2. A *Solution Configuration* dialog box will appear. Click the **Finish** button (with Solution4 selected).

7-1-3. Close all inactive solution windows by selecting **Project > Close Inactive Solution Tabs**.

- 7-1-4. Select function **dct** in the directives pane, right-click on it and select *Insert Directive...*
- 7-1-5. Select **DATAFLOW** directive to improve the throughput.
- 7-1-6. Click on the **Synthesis** button.
- 7-1-7. When the synthesis is completed, the synthesis report is automatically opened.
- 7-1-8. Observe that dataflow type pipeline throughput is listed in the Performance Estimates.




Figure 28. Performance estimate after DATAFLOW directive applied

- The Dataflow pipeline throughput indicates the number of clock cycles between each set of inputs reads (interval parameter). If this value is less than the design latency it indicates the design can start processing new inputs before the currents input data are output.
- Note that the dataflow is only supported for the functions and loops at the top-level, not those which are down through the design hierarchy. Only loops and functions exposed at the top-level of the design will get benefit from dataflow optimization.

- 7-1-9. Scrolling down into the Area Estimates, observe that the number of BRAMs required at the top-level has doubled (from 9 to 18). This is due to the default dataflow ping-pong buffering.




Figure 29. Resource estimate with DATAFLOW directive applied

7-1-10. Look at the console view and notice that `dct_coeff_table` is automatically partitioned in dimension 2. The `buf_2d_in` and `col_inbuf` arrays are partitioned as we had applied the directive in the previous run. The dataflow is applied at the top-level which created channels between top-level functions `read_data`, `dct_2d`, and `write_data`.

```
@I [HLS-10] Checking synthesizability ...
@I [XFORM-502] Unrolling all sub-loops inside loop 'DCT_Outer_Loop' (dct.c:13) in function 'dct_1d' for pipelining.
@I [XFORM-501] Unrolling loop 'DCT_Inner_Loop' (dct.c:15) in function 'dct_1d' completely.
@I [XFORM-102] Partitioning array 'dct_coeff_table' in dimension 2 automatically.
@I [XFORM-101] Partitioning array 'buf_2d_in' (dct.c:81) in dimension 2 completely.
@I [XFORM-101] Partitioning array 'col_inbuf' (dct.c:27) in dimension 2 completely.
@I [XFORM-712] Applying dataflow to function 'dct' (dct.c:78), detected/extracted 3 process function(s):
    'read_data'
    'dct_2d'
    'write_data'.
@I [XFORM-11] Balancing expressions in function 'dct_1d' (dct.c:4)...8 expression(s) balanced.
@I [XFORM-541] Flattening a loop nest 'WR_Loop_Row' (dct.c:71:67) in function 'write_data'.
@I [XFORM-541] Flattening a loop nest 'Xpose_Row_Outer_Loop' (dct.c:38:2) in function 'dct_2d'.
@I [XFORM-541] Flattening a loop nest 'Xpose_Col_Outer_Loop' (dct.c:49:2) in function 'dct_2d'.
@I [XFORM-541] Flattening a loop nest 'RD_Loop_Row' (dct.c:59:67) in function 'read_data'.
@I [HLS-111] Elapsed time: 4.52 seconds; current memory usage: 89.2 MB.
@I [HLS-10] Starting hardware synthesis ...
@I [HLS-10] Synthesizing 'dct' ...
```

Figure 30. Console view of synthesis process after DATAFLOW directive applied

7-2. Perform performance analysis by switching to the Analysis perspective and looking at the `dct` performance profile view.

7-2-1. Switch to the Analysis perspective, expand the Module Hierarchy entries, and select the `dct_2d` entry.

7-2-2. Select the Performance Profile tab.

Observe that most of the latency and interval (throughput) is caused by the `dct_2d` function. The interval of the top-level function `dct`, is less than the sum of the intervals of the `read_data`, `dct_2d`, and `write_data` functions indicating that they operate in parallel and `dct_2d` is the limiting factor. From the Performance Profile tab it can be seen that `dct_2d` is not completely operating in parallel as `Row_DCT_Loop` and `Col_DCT_Loop` were not pipelined.

The screenshot shows two windows from the ZedBoard IDE. The top window is 'Module Hierarchy' and the bottom window is 'Performance Profile'.

	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
dct	4	8	1624	662	507	374	dataflow
dct_read_data	0	0	29	63	66	66	none
dct_dct_2d	2	8	1039	479	373	373	none
dct_write_data	0	0	32	71	66	66	none

	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
dct_dct_2d	-	373	373	-	-
Row_DCT_Loop	no	120	-	15	8
Xpose_Row_Outer_Loop_Xpose_Row_Inner_Loop	yes	64	1	2	64
Col_DCT_Loop	no	120	-	15	8
Xpose_Col_Outer_Loop_Xpose_Col_Inner_Loop	yes	64	1	2	64

(a) ZedBoard

Module Hierarchy							
	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
▲ ● dct	4	8	1680	666	527	392	dataflow
● dct_read_data	0	0	39	64	67	67	none
▶ ● dct_dct_2d	2	8	1078	481	391	391	none
● dct_write_data	0	0	39	72	67	67	none

Performance Profile					
	Pipelined	Latency	Initiation Interval	Iteration Latency	Trip count
▲ ● dct_dct_2d	-	391	391	-	-
● Row_DCT_Loop	no	128	-	16	8
● Xpose_Row_Outer_Loop_Xpose_Row_Inner_Loop	yes	65	1	3	64
● Col_DCT_Loop	no	128	-	16	8
● Xpose_Col_Outer_Loop_Xpose_Col_Inner_Loop	yes	65	1	3	64

(b) Zybo**Figure 31. Performance analysis after the DATAFLOW directive**

One of the limitations of the dataflow optimization is that it only works on top-level loops and functions. One way to have the blocks in `dct_2d` operate in parallel would be to pipeline the entire function. This however would unroll all the loops and can sometimes lead to a large area increase. An alternative is to raise these loops up to the top-level of hierarchy, where dataflow optimization can be applied, by removing the `dct_2d` hierarchy, i.e. inline the `dct_2d` function.

7-2-3. Switch to the *Synthesis* perspective.

Apply INLINE Directive

Step 8

8-1. Create a new solution by copying the previous solution (Solution5) settings. Apply INLINE directive to `dct_2d`. Generate the solution and analyze the output.

8-1-1. Select **Project > New Solution**.

8-1-2. A *Solution Configuration* dialog box will appear. Click the **Finish** button (with Solution5 selected).

8-1-3. Select the function **dct_2d** in the directives pane, right-click on it and select *Insert Directive...*

8-1-4. A pop-up menu shows up listing various directives. Select **INLINE** directive.

The **INLINE** directive causes the function to which it is applied to be inlined: its hierarchy is dissolved.

8-1-5. Click on the **Synthesis** button.

8-1-6. When the synthesis is completed, the synthesis report will be opened.

8-1-7. Observe that the latency reduced from 507 to 407 clock cycles for ZedBoard (527 to 413 clock cycles for Zybo), and the Dataflow pipeline throughput drastically reduced from 374 to 70 clock cycles (392 to 71 clock cycles for Zybo).

8-1-8. Examine the synthesis log to see what transformations were applied automatically.

- The `dct_1d` function calls are now automatically inlined into the loops from which they are called, which allows the loop nesting to be flattened automatically.
- Note also that the DSP48E usage has doubled (from 8 to 16). This is because, previously a single instance of `dct_1d` was used to do both row and column processing; now that the row and column loops are executing concurrently, this can no longer be the case and two copies of `dct_1d` are required: Vivado HLS will seek to minimize the number of clocks, even if it means increasing the area.
- BRAM usage has increased once again (from 36 to 54), due to ping-pong buffering between more dataflow processes.

```
@I [HLS-10] Starting code transformations ...
@I [XFORM-603] Inlining function 'dct_2d' into 'dct' (dct.c:87).
@I [HLS-10] Checking synthesizability ...
@I [XFORM-502] Unrolling all sub-loops inside loop 'DCT_Outer_Loop' (dct.c:13) in function 'dct_1d' for pipelining
@I [XFORM-501] Unrolling loop 'DCT_Inner_Loop' (dct.c:15) in function 'dct_1d' completely.
@I [XFORM-102] Partitioning array 'dct_coeff_table' in dimension 2 automatically.
@I [XFORM-101] Partitioning array 'buf_2d_in' (dct.c:81) in dimension 2 completely.
@I [XFORM-101] Partitioning array 'col_inbuf' (dct.c:27) in dimension 2 completely.
@I [XFORM-721] Changing loop 'Loop_Row_DCT_Loop_proc' (dct.c:32) to a process function for dataflow in function 'd
@I [XFORM-721] Changing loop 'Loop_Xpose_Row_Outer_Loop_proc' (dct.c:38) to a process function for dataflow in fun
@I [XFORM-721] Changing loop 'Loop_Col_DCT_Loop_proc' (dct.c:43) to a process function for dataflow in function 'd
@I [XFORM-721] Changing loop 'Loop_Xpose_Col_Outer_Loop_proc' (dct.c:49) to a process function for dataflow in fun
@I [XFORM-712] Applying dataflow to function 'dct' (dct.c:78), detected/extracted 6 process function(s):
    'read_data'
    'Loop_Row_DCT_Loop_proc'
    'Loop_Xpose_Row_Outer_Loop_proc'
    'Loop_Col_DCT_Loop_proc'
    'Loop_Xpose_Col_Outer_Loop_proc'
    'write_data'.
@I [XFORM-602] Inlining function 'dct_1d' into 'Loop_Row_DCT_Loop_proc' (dct.c:33->dct.c:87) automatically.
@I [XFORM-602] Inlining function 'dct_1d' into 'Loop_Col_DCT_Loop_proc' (dct.c:44->dct.c:87) automatically.
@I [XFORM-11] Balancing expressions in function 'dct_1d' (dct.c:4)...8 expression(s) balanced.
@I [XFORM-11] Balancing expressions in function 'Loop_Row_DCT_Loop_proc' (dct.c:13:61)...8 expression(s) balanced.
@I [XFORM-11] Balancing expressions in function 'Loop_Col_DCT_Loop_proc' (dct.c:13:61)...8 expression(s) balanced.
@I [XFORM-541] Flattening a loop nest 'WR_Loop_Row' (dct.c:71:67) in function 'write_data'.
@I [XFORM-541] Flattening a loop nest 'RD_Loop_Row' (dct.c:59:67) in function 'read_data'.
@I [XFORM-541] Flattening a loop nest 'Row_DCT_Loop' (dct.c:32:66) in function 'Loop_Row_DCT_Loop_proc'.
```

Figure 32. Console view after `INLINE` directive applied to `dct_2d`

8-1-9. Switch to the Analysis perspective, expand the Module Hierarchy entries, and select the `dct` entry.

Observe that the `dct_2d` entry is now replaced with `dct_Loop_Row_DCT_Loop_proc`, `dct_Loop_Xpose_Row_Outer_Loop_proc`, `dct_Loop_Col_DCT_Loop_proc`, and `dct_Loop_Xpose_Col_Outer_Loop_proc` since the `dct_2d` function is inlined. Also observe that all the functions are operating in parallel, yielding the top-level function interval (throughput) of 70 clock cycles.

	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
▲ ● dct	6	16	2555	668	407	70	dataflow
● dct_read_data	0	0	29	63	66	66	none
● dct_Loop_Row_DCT_Loop_proc	0	8	694	149	69	69	none
● dct_Loop_Xpose_Row_Outer_Loop_proc	0	0	29	65	66	66	none
● dct_Loop_Col_DCT_Loop_proc	0	8	694	149	69	69	none
● dct_Loop_Xpose_Col_Outer_Loop_proc	0	0	30	73	66	66	none
● dct_write_data	0	0	32	71	66	66	none

(a) ZedBoard

Module Hierarchy							
	BRAM	DSP	FF	LUT	Latency	Interval	Pipeline type
▲ dct	6	16	2628	672	413	71	dataflow
● dct_read_data	0	0	39	64	67	67	none
● dct_Loop_Row_DCT_Loop_proc	0	8	711	149	70	70	none
● dct_Loop_Xpose_Row_Outer_Loop_proc	0	0	41	66	67	67	none
● dct_Loop_Col_DCT_Loop_proc	0	8	711	149	70	70	none
● dct_Loop_Xpose_Col_Outer_Loop_proc	0	0	40	74	67	67	none
● dct_write_data	0	0	39	72	67	67	none

(b) Zybo**Figure 33. Performance analysis after the INLINE directive**

8-1-10. Switch to the *Synthesis* perspective.

Apply RESHAPE Directive**Step 9**

9-1. Create a new solution by copying the previous solution (Solution6) settings. Apply the RESHAPE directive. Generate the solution and understand the output.

9-1-1. Select **Project > New Solution**.

9-1-2. A *Solution Configuration* dialog box will appear. Click the **Finish** button (with Solution6 selected).

9-1-3. Select **PARTITION** directive applied to the **buf_2d_in** array of the **dct** function in the Directive pane, right-click, and select **Modify Directive**. Select **ARRAY_RESHAPE** directive, enter 2 as the dimension, and click **OK**.

9-1-4. Similarly, change **PARTITION** directive applied to the **col_inbuf** array of the **dct_2d** function in the Directive pane, to **ARRAY_RESHAPE** with the dimension of **2**.

9-1-5. Assign the **ARRAY_RESHAPE** directive with dimension of 2 to the **dct_coeff_table** array.

```

  ▲ ● dct_1d
    ×|1| dct_coeff_table
    % HLS ARRAY_RESHAPE variable=dct_coeff_table dim=2
    ▷ */? DCT_Outer_Loop
  ▲ ● dct_2d
    % HLS INLINE
    ×|1| row_outbuf
    ×|1| col_outbuf
    ×|1| col_inbuf
    % HLS ARRAY_RESHAPE variable=col_inbuf dim=2
    */? Row_DCT_Loop
    ▷ */? Xpose_Row_Outer_Loop
    */? Col_DCT_Loop
    ▷ */? Xpose_Col_Outer_Loop
  ▷ ● read_data
  ▷ ● write_data
  ▲ ● dct
    % HLS DATAFLOW
    ● input
    ● output
    ×|1| buf_2d_in
    % HLS ARRAY_RESHAPE variable=buf_2d_in dim=2
    ×|1| buf_2d_out

```

Figure 34. RESHAPE directive applied

- 9-1-6.** Click on the **Synthesis** button.
- 9-1-7.** When the synthesis is completed, the synthesis report is automatically opened.
- 9-1-8.** Observe that both latency (increased from 407 to 535 for ZedBoard and from 413 to 541 for Zybo) and Dataflow pipeline throughput (increased from 70 to 131 for ZedBoard and 71 to 132 for Zybo) has regressed. The BRAM resource utilization increased from 6 to 22 for ZedBoard and increased from 6 to 22 for Zybo.
- Reviewing the synthesis log will provide some clues. There are warnings in the scheduling phase for `read_data` stating that `II=1` could not be achieved. In fact, `read_data` complains about the conflict of read and write operations.
 - The problem here is due to the fact that an update to a single element in a reshaped array requires that the entire word be read, the single element updated and the entire word written back: an array that has been reshaped requires a read-modify-write cycle (Vivado HLS does not implement byte-masking on writes).
 - This operation negatively impacts the maximum write bandwidth for such an array.
- 9-1-9.** Thus it can be seen the directives have to be applied carefully.
- 9-1-10.** Close Vivado HLS by selecting **File > Exit**.

Conclusion

In this lab, you learned various techniques to improve the performance and balance resource utilization. PIPELINE directive when applied to outer loop will automatically cause the inner loop to unroll. When a loop is unrolled, resources utilization increases as operations are done concurrently. Partitioning memory may improve performance but will increase BRAM utilization. When INLINE directive is applied to a function, the lower level hierarchy is automatically dissolved. When DATAFLOW directive is applied, the default memory buffers (of ping-pong type) are automatically inserted between the top-level functions and loops. The RESHAPE directive will allow multiple accesses to BRAM, however, care should be taken if a single element requires modification as it will result in read-modify-write operation for the entire word. The Analysis perspective and console logs can provide insight on what is going on.

Answers

1. Answer the following questions for dct:

Estimated clock period:	<u>6.38 ns</u>
Worst case latency:	<u>3959 clock cycles</u>
Number of DSP48E used:	<u>1</u>
Number of BRAMs used:	<u>5</u>
Number of FFs used:	<u>272</u>
Number of LUTs used:	<u>390</u>